

Multilite



507

Multilite

Emergency Luminaires & Exit Signs
Surface Mounted, Single or Double Sided

Specifications

Application	Escape Sign
Mounting	Direct mounting to wall & ceiling. Suspended, recessed & flag mounting are available by accessories
Type	Manual Test, Self Test, DALI, Central
Mode	Selectable maintained/non-maintained
Emergency Duration	Selectable 1/2/3/8 hours
Viewing Distance	23m, 30m, single & double sided
Light Source	LED module, 20 mid power leds, 6500K, CRI>80
Battery	Ni-Cd, Ni-MH, Li-FePO4
Wiring	Up to 2x2,5 mm ² quick fit terminal block
Cable Entry	Two easy breakable entry holes rear & upper part
Power Supply	230 Volt, 50/60Hz
Protection	IP40
Temperature Range	5-40°C
Electrical Class	Class II (no earth wiring required)
Material	White polycarbonate housing

Ordering Details

Multilite 23 Series (23m Viewing Distance)

Code	Type	Battery		Viewing Distance
		Type	Volt-Ah	
MTL-SM23E-LF	ECO	Li-FePO4	3.2V-1.6Ah	23m
MTL-SM23HE-LF				
MTL-SM23E		Ni-Cd	3.6V-0.8Ah	
MTL-SM23HE				
MTL-SM23ST-LF	ST	Li-FePO4	3.2V-1.6Ah	
MTL-SM23HST-LF				
MTL-SM23ST-MH		Ni-MH	3.6V-1.5Ah	
MTL-SM23HST-MH				
MTL-SM23ST		Ni-Cd	3.6V-0.8Ah	
MTL-SM23HST				
MTL-SM23DALI-LF	DALI	Li-FePO4	3.2V-1.6Ah	
MTL-SM23HDALI-LF			3.2V-3.8Ah	
MTL-SM23E-DALI		Ni-Cd	3.6V-0.8Ah	
MTL-SM23H-DALI			3.6V-1.5Ah	
MTL-SM23DALI		Ni-MH	3.6V-2.2Ah	
MTL-SM23D				



Multilite 30 Series (30m Viewing Distance)

Code	Type	Battery		Viewing Distance
		Type	Volt-Ah	
MTL-SM30E-LF	ECO	Li-FePO4	3.2V-1.6Ah	30m
MTL-SM30HE-LF				
MTL-SM30E		Ni-Cd	3.6V-0.8Ah	
MTL-SM30HE				
MTL-SM30ST-LF	ST	Li-FePO4	3.2V-1.6Ah	
MTL-SM30HST-LF				
MTL-SM30ST-MH		Ni-MH	3.6V-1.5Ah	
MTL-SM30HST-MH				
MTL-SM30ST		Ni-Cd	3.6V-0.8Ah	
MTL-SM30HST				
MTL-SM30DALI-LF	DALI	Li-FePO4	3.2V-1.6Ah	
MTL-SM30HDALI-LF			3.2V-3.8Ah	
MTL-SM30E-DALI		Ni-Cd	3.6V-0.8Ah	
MTL-SM30H-DALI			3.6V-1.5Ah	
MTL-SM30DALI		Ni-MH	3.6V-2.2Ah	
MTL-SM30D				

Accessories	Description of Spare Parts
MTL-REC	Recessed mounting set
MTL-FLAG	Flag mounting set
MTL-SSWR-2M	Suspended type hanging set (2m)
MTL23-SET	Sign set - 23m Viewing distance
MTL-23-LFT	Sign pad - 23m, left side
MTL-23-RGT	Sign pad - 23m, right side
MTL-23-UP	Sign pad - 23m, up side
MTL-23-DWN	Sign pad - 23m, down side
MTL-23-PAD	Sign pad - 23m, white pad
MTL30-SET	Sign set - 30m Viewing distance
MTL-30-LFT	Sign pad - 30m, left side
MTL-30-RGT	Sign pad - 30m, right side
MTL-30-UP	Sign pad - 30m, up side
MTL-30-DWN	Sign pad - 30m, down side
MTL-30-PAD	Sign pad - 30m, white pad
MTL-CLP-SET	Mounting clips set



Dimensions (mm)



Viewing Distance

