

Elegance Slim



Elegance Slim

Emergency Luminaires & Exit Signs
Surface Mounted, Single Sided

General Specifications

Application	Escape Sign, Anti-Panic Lighting, Escape Route Lighting, Hazardous Area Lighting
Mounting	Direct mounting to wall & ceiling. Recessed mounting is available by accessory
Type	Manual Test, Auto Test, DALI2, Wireless, Central
Operating Mode	Selectable maintained/ non-maintained
Emergency Duration	Selectable 1/3 hours
Viewing Distance	23m
Light Source	12 mid power led module, 6500K, CRI>80
Battery	Li-FePO4
Warranty	5 years



Technical Specifications

Supply Voltage	220-240 Volt, 0/50-60 Hz
Battery	3.2 Volt Li-FePO4
Charger	Smart charger circuit
Charge Indicator	Green LED lamp
Fault Indicator	Red LED lamp
Insulation Class	Class II
Protection Class	IP65
Impact Protection Rating	IK10
Temperature	ta 0 / +40°C
Terminals	Up to 2x2,5mm ² quick fit terminal block
Cable Entry	Breakable entry holes back, rear & top parts
Enclosure	White polycarbonate housing


Li-FePO4 Batteries & Management

- Multi level smart charge system.
- Integrated open / short circuit protection.
- Integrated low / high temperature protection.
- Integrated overcharge / overdischarge protection.
- Integrated deep discharge protection.
- Polarity reversal protection for battery provided by 3-pole connector.
- Up to 10 year design life.

Standards

- EN 60598-1
- EN 60598-2-22
- EN 62031
- EN 62384
- EN 55015
- EN 61000-3-2
- EN 61000-3-3
- EN 61547
- IEC 62133-2 (related to battery)
- IEC 62620 (related to battery)
- According to EN 1838 (Application)
- According to EN 50172 (Application)
- According to EN 62034 (Auto Test)
- According to EN 62386 (DALI)

Dimensions (mm)



Standard Signs



Ordering Details

Code	Lumen Output		Li-FePO4 Battery	Type
	1H	3H		
ELGS16-E	250 Lumen	140 Lumen	3.2V -1.6Ah	Manual Test
ELGS20-E	250 Lumen	180 Lumen	3.2V -2.0Ah	
ELGS32-E	-	250 Lumen	3.2V -3.2Ah	
ELGS16-AT	250 Lumen	140 Lumen	3.2V -1.6Ah	Auto Test
ELGS20-AT	250 Lumen	180 Lumen	3.2V -2.0Ah	
ELGS32-AT	-	250 Lumen	3.2V -3.2Ah	
ELGS16-DALI	250 Lumen	140 Lumen	3.2V -1.6Ah	DALI-2
ELGS20-DALI	250 Lumen	180 Lumen	3.2V -2.0Ah	
ELGS32-DALI	-	250 Lumen	3.2V -3.2Ah	
ELGS-16-LUM	250 Lumen	140 Lumen	3.2V -1.6Ah	Wireless
ELGS-32-LUM	-	250 Lumen	3.2V -3.2Ah	
ELGS-CBE	250 Lumen		-	Central-Eco
ELGS-CBDALI	250 Lumen		-	Central-DALI
ELGS-HP-CBDALI	1000 Lumen		-	

Accessories	Explanations
ELGS-PAD-LEFT	Sign pad, LEFT side
ELGS-PAD-RIGHT	Sign pad, RIGHT side
ELGS-PAD-UP	Sign pad, UP side
ELGS-PAD-DOWN	Sign pad, DOWN side
ELGS-PAD-OPAL	Opal pad
ELGS-SIGN-SET1	Sign set, LEFT, RIGHT, UP, DOWN side & opal pad
ELGS-REC-SET	Recessed mounting set
ELGS-PERSPEX-SET	Perspex sign set
ELGS-PRGRID	Protection grid